







Head Office Address: No.858, Meysam 2 St, Payam Blvd, Karaj, IRAN
P.O BOX: 31991-89200 | Tel: +98(26) 3559 | Fax: +98(26)34802899
Factory Address: Bagh Falak Ave, Km 11 Bistoon Rd, Kermanshah, IRAN
P.O BOX: 67441-31933 | Tel: +98(83) 34733310-17 | Fax: +98(83)34733319

www.bistoontile.com | info@bistoontile.com

## Polished Collection

Golden Calcutta White Size: 600x1200mm Thickness: 9mm Body: Porcelain - White Body

Porcelain tile reinvents itself by creating a new living style in which tradition becomes a source of inspiration for a contemporary look.

Polished porcelain tiles have an additional liquid glass coating applied to their surface, which is between 5-7 microns thick. Glossy porcelain tiles are lighter and thinner than unglazed porcelain ones. Glaze quality has a bearing on the lifespan of the glossed porcelain tile. Bright glazes are denser than dark ones when fired at a high temperature. Polished porcelain tile, which has an additional layer of glass on it, is one of the most moisture-resistant goods. Porcelain tiles with a high sheen and low porosity are common.



Porcelain | Different color | Rectified | Anti Slip | White Body



Effect: Nano Polished Size: 600x1200mm Thickness: 9mm Faces: 6

### Golden Calcutta White

# pristine collection for mesmerizing designs

Calcutta Gold Marble is a kind of white marble quarried in Italy. This stone is especially good for Countertops, mosaic, wall and floor applications, fountains, pool and wall capping, stairs, window sills and other design projects. It also called Calacatta Gold Marble, Calacatta Golden Marble, Calacatta Marble, Calacutta Gold Marble, Calacutta White Marble, Calcutta Golden Marble . Calcutta White Marble can be processed into Honed, Aged, Polished, Sawn Cut, Sanded, Rockfaced, Sandblasted, Bushhammered, Tumbled, Weatheredge and so on.

#### Technical Information

Working Size	600x1200mm
Nominal Size	600x1200mm
Approximate Area	1.44m²
Number of Tile in Each Carton	2
Type of Use	Indoor Floor
Chemical Resistance	GLB - GB
Resistance to Stain	Class 3
Carton Weight	30Kg
Construction Method	Dry Pressing
Surface Type	Glaze (GL)
Thickness	9 +- 0.5
Water Absorption	BIIa
Absorption Class	2

#### Packing List

Pallet specifications	1100x1100 mm
Pcs/Box	2
M²/Box (m²)	1.44
Kg/Box (kg)	30
Box/Pallet	67
M²/Pallet (m²)	96.48
Kg/Pallet (kg)	1950-2000
 Kg/M² (kg)	20
Kg/Pcs (kg)	14.75
Pallet Dimensions (m³)	110.110.134
Thick/Pcs (mm)	9 +- 0.5
Pallet/Truck	13-14

## Family Is a Value

www.bistoontile.com

Follow "Bistoon Tile" Social Networks

